

ULTRAFAB^{INC.}

1050 HOOK ROAD, FARMINGTON, NY
PHONE: (716) 924-2186
FAX: (716) 924-7680

MATERIAL SAFETY DATA SHEET
DATE PREPARED: 12/03/97

IDENTITY: Weatherstripping (component parts)

HAZARDOUS INGREDIENTS/IDENTITY INFORMATION: Ingredient name: Polypropylene

PHYSICAL/CHEMICAL CHARACTERISTICS:

Appearance: White milky color, gray, black, beige, brown Odor: No specific odor Boiling point: Not available
Vapor Pressure: Not applicable Vapor density: (Air = 1.0) Not applicable Solubility in water: Insoluble
Melting point: 160-166 °C (320-330 °F) Specific gravity: (Water = 1.0) <1 Evaporation rate: Not applicable

FIRE AND EXPLOSION HAZARD DATA:

Flash Point: Not applicable Flammable limits: Not available Extinguishing media: Water spray, dry chemical.
Special firefighting procedures: Self contained breathing apparatus, protective clothing. Unusual fire and explosion hazards: none

REACTIVITY DATA:

Stability: Stable Hazardous Polymerization: none
Incompatibility and Hazardous Decomposition: Avoid Moisture and strong oxidizing agents

HEALTH HAZARD DATA:

Skin: Not found to be a sensitizer. Eyes: Avoid contact Inhalation: Not respirable in this form.
Ingestion: Not a probable route of exposure. Health Hazard (acute/chronic): non-toxic under normal use
Carcinogenicity: Not listed or regulated by ACGIH, NTP, OR OSHA Signs or Symptoms of Exposure: none identified
Emergency and First Aid Procedures: If irritation of eyes or skin occurs flush with running water. If discomfort continues seek medical attention.

PRECAUTIONS for SAFE HANDLING and USE:

Spills: Sweep or vacuum and place in containers for disposal to an approved landfill
Waste Disposal Method: Dispose of as non-hazardous waste.
Precautions to be Taken in Handling and Storing: No special requirements.
Other Precautions: none

CONTROL MEASURES:

Respiratory Protection: A dust mask should be worn if dusty conditions exist.
Ventilation: Mechanical ventilation should be used during processing to remove any dust, mist, or vapors which may be generated.
Protective Clothing or Equipment: Safety glasses



MATERIAL SAFETY DATA SHEET

SANTOPRENE® THERMOPLASTIC UV RUBBER GRADES

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

ADVANCED ELASTOMER SYSTEMS, L.P.
388 South Main Street
Akron, Ohio 44311

EMERGENCY TELEPHONE NUMBER
800-424-9300 (CHEMTREC)

Product Identification:

121-58	121-73-W175	221-55	221-87
121-58-W175	121-80	221-64W175	221-87W211
121-64-W175	121-87	221-73	223-50
121-67	123-40	221-73-W175	
121-67-W175	123-50	221-80	

2. COMPOSITION/INFORMATION ON INGREDIENTS

SANTOPRENE thermoplastic rubber grades are proprietary products. Their composition is trade secret information of Advanced Elastomer Systems, L.P. These products are not identified by CAS number. All components of these products appear on the Inventory of Chemical Substances published by the U.S. Environmental Protection Agency or qualify for the TSCA polymer exemption under U.S. Federal Register Vol. 60, No. 60, 3/29/95. New Jersey Trade Secret Registry No.: 01122800003-5001P

<u>Components:</u>	<u>CAS. NO.</u>	<u>Airborne Exposure Limits</u>		<u>Weight Percent</u>
		<u>OSHA PEL</u>	<u>ACGIH PEL</u>	
Thermoplastic rubber	Mixture	None established	None established	100%
Components within Polymer Matrix:				
Carbon black	1333-86-4	3.5 mg/m ³ TWA	3.5 mg/m ³	2 to 3%

Black grades contain carbon black, CAS No. 1333-86-4, within the polymer matrix. The International Agency for Research on Cancer (IARC) has determined that carbon black is possibly carcinogenic to humans (IARC Group 2B). IARC determined that there is inadequate evidence in humans but sufficient evidence in SANTOPRENE animals for carcinogenicity of carbon black.

3. HAZARDS IDENTIFICATION

Emergency Overview:

HANDLE PELLETS IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES. THESE PRACTICES INCLUDE AVOIDING UNNECESSARY EXPOSURE AND REMOVAL OF THE MATERIAL FROM EYES, SKIN AND CLOTHING.

CAUTION! PROCESSING RELEASES VAPORS OR FUMES WHICH MAY CAUSE RESPIRATORY TRACT IRRITATION

Appearance: Black or natural (colorable) pellets.

Odor: Slightly rubberlike.

Avoid breathing processing fumes or vapors.

Process using adequate ventilation.

Potential Health Effects:

INHALATION: Inhalation of fumes or vapors during processing may cause respiratory tract irritation.

EYE CONTACT: Pellets do not cause significant eye irritation.

SKIN CONTACT: Pellets do not cause significant skin irritation.

4. FIRST AID MEASURES

INHALATION: If fumes are inhaled, remove to fresh air. If breathing is difficult, get medical attention.

5. FIRE FIGHTING MEASURES

Flash (piloted) Ignition Temperature: >650°F (343°C)

Method: ASTM D 1929-77



MATERIAL SAFETY DATA SHEET

SANTOPRENE® THERMOPLASTIC UV RUBBER GRADES

Self-Ignition (non-piloted) Temperature: >700°F (371°C) Method: ASTM D 1929-77

Extinguishing Media: Water spray or any Class A extinguishing agent.

Special Firefighting Procedures: Firefighters and others exposed to products of combustion should wear self-contained breathing apparatus and full protective clothing. Carbon monoxide is liberated as a toxic decomposition product when SANTOPRENE thermoplastic rubber is ignited.

Unusual Fire and Explosion Hazards: None known.

6. ACCIDENTAL RELEASE MEASURES

Spilled product may cause a slipping hazard.

IN CASE OF SPILL OR LEAK, vacuum or sweep up and place in clean, covered containers for recycle or disposal.

7. HANDLING AND STORAGE

Avoid leaving container open for prolonged periods to prevent exposure to humidity. SANTOPRENE thermoplastic rubber will pick up small amounts of moisture. Store in a cool, dry place. Usual precautions in pellet handling should be observed to prevent contamination by dirt or other materials.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection: SANTOPRENE thermoplastic rubber does not cause significant eye irritation or eye toxicity requiring special protection. Use good industrial practice to avoid eye contact.

Skin Protection: Although SANTOPRENE thermoplastic rubber does not present significant skin concern, minimize skin contamination by following good industrial hygiene practice. Wearing protective gloves is recommended. Wash hands and contaminated skin thoroughly after handling.

Respiratory Protection: Avoid breathing process vapors or dust. Use NIOSH approved respiratory protection equipment (full facepiece recommended) when airborne exposure is excessive. Consult respirator manufacturer to determine appropriate type equipment for given application. Observe respirator use limitations specified by NIOSH or the manufacturer. Respiratory protection programs must comply with 29 CFR 1910.134.

Ventilation: Provide natural or mechanical ventilation to minimize exposure. If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity: 0.95 to 0.98

Hardness: 45 Shore A to 50 Shore D

NOTE: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specifications for the product.

10. STABILITY AND REACTIVITY

Stability: Thermally stable to 500°F (260°C).

Materials to Avoid: SANTOPRENE thermoplastic rubber may react with strong oxidizing chemicals. SANTOPRENE thermoplastic rubber also reacts with acetal resins at temperatures of 425°F (218°C) and above, producing decomposition of the acetal resin, and formaldehyde as a decomposition product. Decomposition of halogenated polymers and reactive phenolic resins may also be accelerated when they are in contact with SANTOPRENE thermoplastic rubber at processing temperatures. Thoroughly purge processing equipment with polyolefin polymers, including polypropylene, when using the same equipment to process SANTOPRENE thermoplastic rubber and acetal resins, halogenated polymers and phenolic resins. Do not mix SANTOPRENE acetal resins, halogenated polymers or reactive phenolic resins at elevated temperatures.





MATERIAL SAFETY DATA SHEET

SANTOPRENE® THERMOPLASTIC UV RUBBER GRADES

Hazardous Decomposition Products: Smoke, carbon monoxide, Carbon monoxide, and possibly hydrocarbons may evolve when processing temperatures exceed 500°F (260°C) or when SANTOPRENE thermoplastic rubber is ignited.

Hazardous Polymerization: Does not occur.

11. TOXICOLOGICAL INFORMATION

The following information summarizes human experience and results of scientific investigations reviewed by health professionals for hazard evaluation of SANTOPRENE thermoplastic rubber and development of Precautionary Measures and Occupational Control Procedures recommended in this document.

Effects of Exposure

Skin contact is expected to be the primary route of occupational exposure to SANTOPRENE thermoplastic rubber. Occupational exposure to this material in normal handling and storage has not been reported to cause significant adverse human health effects. Due to its chemical and physical properties, SANTOPRENE thermoplastic rubber does not appear to possess any toxicological properties which would require special handling other than the good industrial hygiene and safety practices employed with any industrial material of this type.

However, under normal processing conditions, this product will release fumes and vapors. Components of these releases may vary with processing times and temperatures and therefore specific composition cannot be predicted based on current information. These process releases may produce respiratory tract irritation where such releases are allowed to build up due to inadequate ventilation in the general work area. These fumes and vapors, with repeated and prolonged exposure at high concentrations, could cause nausea, drowsiness and headache, especially if such exposures exceed current exposure limits (where established). Good industrial hygiene and safety practices should be used to avoid unnecessary exposures.

Toxicological Data

Results of single exposure (acute) animal studies conducted on a representative grade of general purpose thermoplastic rubber indicate that these materials are practically nontoxic orally (rats) and after skin application (rabbits). They are practically nonirritating to rabbit eyes and skin.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

When discarded, SANTOPRENE thermoplastic rubber is not a "hazardous waste" as that term is defined in 40 CFR 261, "Identification and Listing of Hazardous Waste." Recycle or burn in an approved incinerator or dispose of in an approved chemical landfill in accordance with all applicable local, state and federal laws and regulations. Consult your attorney or appropriate regulatory officials for information on such disposal. Reprocess only uncontaminated material.

Spill or Leakage Procedures: Vacuum or sweep up and place in container for recycle or disposal as recommended above.

Containers: Recycle or burn in an approved incinerator or dispose of in an approved chemical landfill in accordance with all applicable local, state and federal laws and regulations.

14. TRANSPORT INFORMATION

DOT Proper Shipping Name: Not Applicable

DOT Hazard Class/I.D. No.: Not Applicable

DOT Label: Not Applicable

U.S. Surface Freight Classification -

Rail: Rubber, Synthetic Crude

Truck: Rubber, Crude

15. REGULATORY INFORMATION

Reportable Quantity (RQ) Under



MATERIAL SAFETY DATA SHEET
SANTOPRENE® THERMOPLASTIC UV RUBBER GRADES

DOT (49 CFR) and CERCLA Regulations: Not Applicable

SARA Hazard Notification

Hazard Categories under criteria of
SARA Title III rules (40 CFR Part 370): Not Applicable.

Section 313 Hazardous Chemical(s): Not Applicable.

**SECTION 313 INFORMATION MUST BE INCLUDED IN ALL MSDSs
THAT ARE COPIED AND DISTRIBUTED FOR THIS MATERIAL.**

Hazardous Chemical(s) under OSHA Hazard Communication Standard:

Black grades contain Carbon Black

2 to 3% Weight Range

HMIS Rating: Reactivity: 1

Health: 1

Flammability: 1

16. OTHER INFORMATION

Date MSDS Initially Prepared: 05/26/95

Revision(s): 09/23/96 - Updated carbon black information

10/11/96 - Updated polymer exemption information

12/21/99 - Y2K Update

FOR ADDITIONAL NON-EMERGENCY INFORMATION, CONTACT:

Product Safety
(330) 849-5163

DISCLAIMER OF WARRANTY AND LIABILITY: Although the information and recommendations set forth herein ("Information") are believed to be correct, ADVANCED ELASTOMER SYSTEMS, L.P., AND ITS AFFILIATES MAKE NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, AS TO THE ACCURACY OR COMPLETENESS THEREOF, OR OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE REGARDING INFORMATION, OR ANY PRODUCT, PROCESS OR EQUIPMENT OF ADVANCED ELASTOMER SYSTEMS, L.P., AND ITS AFFILIATES, OR OF ANY OTHER MANUFACTURER OR SUPPLIER MENTIONED HEREIN. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent. ADVANCED ELASTOMER SYSTEMS, L.P., AND ITS AFFILIATES MAKE NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ANY PATENT. Persons receiving Information must make their own determination as to its suitability to their purposes prior to use. In no event will Advanced Elastomer Systems, L.P., or its affiliates be responsible for damages of any nature whatsoever resulting from the use of or reliance upon Information or the products, processes or equipment to which Information refers.

VISTAFLEX® is a trademark of Exxon Corporation, licensed to Advanced Elastomer Systems, L.P.

